

FITTINGS

MATERIAL:

All fittings are formed in punch press dies from mild, pickled and oiled, bar or strip steel. Plain or electro-galvanized fittings meet the requirements for ASTM A575 and A-576, or ASTM A-36.

STANDARD DIMENSIONS:

Standard dimensions on all fittings are as follows except where otherwise indicated:

Fitting Thickness: $\frac{1}{4}$ "
Fitting Width: $1\frac{5}{8}$ "
Hole Diameter: $\frac{9}{16}$ "
Hole Spacing: $1\frac{7}{8}$ " on centers and $1\frac{3}{16}$ " from ends.

STANDARD FINISH:

All fittings are available in painted green or electro-galvanized finish.

ORDERING INFORMATION:

When ordering, add the length or size and finish to the part number.

SET SCREW TORQUE:


BOLT SIZE	$\frac{1}{4}$ "-20	$\frac{5}{16}$ "-18	$\frac{3}{8}$ "-16	$\frac{1}{2}$ "-13	$\frac{5}{8}$ "-11	$\frac{3}{4}$ "-10
Set Screw Torque In/Lbs	40	60	125	250	400	665

Note: Caution should be taken not to overtighten the set screw

FITTINGS

Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish


CS 619 – Square Washer



Note: Indicate rod size when ordering.
For example, CS 619 1/2.

Rod Size	Hole Size	Wt./100 pcs
1/4"	1 1/32"	18
3/8"	7/16"	18
1/2"	9/16"	17
5/8"	1 1/16"	16
3/4"	1 3/16"	15


CS 2504 – Guided Square Washer



Note: Indicate rod size when ordering.
For example, CS 2504 1/2.


Rod Size	Hole Size	Wt./100 pcs
1/4"	1 1/32"	18
3/8"	7/16"	18
1/2"	9/16"	17

CS 618 – Two-Hole Swivel Plate




Weight/100 pcs: 55 lbs.

CS 889 – Five-Hole Splice Plate




Weight/100 pcs: 94 lbs.

CS 617 – Three-Hole Swivel Plate




Weight/100 pcs: 75 lbs.

CS 718 – Flat Angle Plate




Weight/100 pcs: 58 lbs.

CS601 – Two-Hole Splice Plate




Weight/100 pcs: 38 lbs.

CS 602 – Three-Hole Splice Plate




Weight/100 pcs: 50 lbs.

CS 888 – Four-Hole Splice Plate




Weight/100 pcs: 78 lbs.

CS 719 – Flat Angle Plate




Weight/100 pcs: 80 lbs.

CS 620 – Two-Hole Connecting Plate




Weight/100 pcs: 35 lbs.

CS 621 – Four-Hole Connecting Plate




Weight/100 pcs: 73 lbs.

CS 714 – Tee Plate




Weight/100 pcs: 80 lbs.

CS 712 – Cross Plate




Weight/100 pcs: 105 lbs.

CS 744 – Flat Corner Connector




Weight/100 pcs: 70 lbs.

CS 750 – Four-Hole Corner Connector




Weight/100 pcs: 105 lbs.

CS 2190 – Flat Corner Connector




Weight/100 pcs: 150 lbs.

CS 925 – Three-Hole Joint Connector




Weight/100 pcs: 70 lbs.

CS 747 – Symmetrical Four-Hole Connector




Weight/100 pcs: 105 lbs.

CS 854 – Flat Connector




Weight/100 pcs: 148 lbs.

CS 2112 – Cross Connector



Weight/100 pcs: 240 lbs.

CS 822 – Double 45° Connector




Weight/100 pcs: 112 lbs.

FITTINGS


Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish

CS 921 – One-Hole Angle




Part No.	L	Wt./100 pcs
CS 921 A	3 7/8"	61
CS 921 B	5 7/8"	84
CS 921 C	7 7/8"	107
CS 921 D	9 7/8"	130

CS 806 – Self-Aligning Two-Hole Angle




Weight/100 pcs: 40 lbs.

CS 605 – Three-Hole Corner Angle




Weight/100 pcs: 58 lbs.

CS 603 – Two-Hole End Angle




Weight/100 pcs: 38 lbs.

CS 2144 – Corner Angle




A	Wt./100 pcs
3"	49
3 1/2"	54
4"	61

CS 2520 – Slotted 90° Angle




Weight/100 pcs: 42 lbs.

CS 604 – Two-Hole Corner Angle




Weight/100 pcs: 38 lbs.

CS 763 – Slotted Adjustment Angle




Weight/100 pcs: 65 lbs.

CS 764 – Slotted Adjustment Angle




Weight/100 pcs: 85 lbs.

CS 2545 – Slotted 90° Angle




Weight/100 pcs: 38 lbs.

CS 3049 – Two-Hole Slotted 90° Angle




Weight/100 pcs: 66 lbs.

CS 607 – Four-Hole Corner Angle




Weight/100 pcs: 78 lbs.

CS 614 – Four-Hole Joint Angle Connector



Weight/100 pcs: 103 lbs.


CS 716 R or L – Angle Tee Plate



Note:
Specify R (Right) or L (Left) Right Hand Illustrated


Weight/100 pcs: 80 lbs.

CS 606 – Three-Hole Corner Angle




Weight/100 pcs: 58 lbs.

CS 660 – Four-Hole Corner Angle




Weight/100 pcs: 78 lbs.

CS 615 – Five-Hole Joint Angle Connector




Weight/100 pcs: 135 lbs.

CS 713 – Cross Plate Angle




Weight/100 pcs: 105 lbs.

CS 745 – Three-Hole Corner Angle




Weight/100 pcs: 58 lbs.

CS 3373 – Universal Corner Connector



Weight/100 pcs: 134 lbs.


CS 720 R or L – Angle Plate Connector



Note:
Specify R (Right) or L (Left) Right Hand Illustrated

Weight/100 pcs: 55 lbs.

CS 715 – Tee Plate 90° Angle




Weight/100 pcs: 71 lbs.

FITTINGS


Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish

CS 689A, CS 689B – Double-Slotted Corner Connector




Part No.	A	B	Wt./100 pcs
CS 689 A	6 $\frac{5}{8}$ "	4"	190
CS 689 B	8 $\frac{5}{8}$ "	6"	242

CS 927 – Five-Hole Corner Connector



Weight/100 pcs: 154 lbs.


CS 2007 R or L – Six-Hole Corner Connector



Note:
Specify R (Right) or L (Left) Right Hand Illustrated


Weight/100 pcs: 160 lbs.

CS 748 – Four-Hole Corner Joint Connector




Weight/100 pcs: 105 lbs.

CS 746 – Three-Hole Corner Joint Connector



Weight/100 pcs: 70 lbs.


CS 752 R or L – Four-Hole Corner Connector



Note:
Specify R (Right) or L (Left) Right Hand Illustrated

Weight/100 pcs: 105 lbs.

CS 3326 R or L – Six-Hole Gussetted Corner Connector




Continuous Weld

Note:
Specify R (Right) or L (Left) Right Hand Illustrated


Weight/100 pcs: 230 lbs.

CS 2113 – Slotted Corner Connector




Weight/100 pcs: 97 lbs.

CS 622 – Four-Hole Corner Connector



Weight/100 pcs: 75 lbs.


CS 624 – Two-Hole Closed Angle Connector



Weight/100 pcs: 58 lbs.

"B" In.	"A" Angle
3"	37 $\frac{1}{2}$ °
3 $\frac{1}{8}$ "	45°
3 $\frac{1}{16}$ "	52 $\frac{1}{2}$ °
3 $\frac{1}{8}$ "	60°
3 $\frac{1}{8}$ "	67 $\frac{1}{2}$ °
3 $\frac{3}{16}$ "	75°
3 $\frac{3}{16}$ "	82 $\frac{1}{2}$ °

CS 926 – Strut Brace




A Size	Wt./100 pcs
12"	160
18"	218
24"	280

FITTINGS

Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish


CS 633 – Two-Hole Open Angle Connector



"A" Degree	"B" In.	"C" In.
82½°	3¾"	1 11/16"
75°	3¾"	
67½°	3½"	1¾"
60°	3¾"	1 7/8"
52½°	3¼"	2 1/16"
45°	3"	2 5/16"
37½°	2 11/16"	2 5/8"
30°	3¼"	2 1/16"
22½°	3 5/16"	
15°	3 5/16"	
7½°	3 5/16"	

Weight/100 pcs: 58 lbs.


CS 2054 – Corner Connector



Use With: CS 200, CS 210

Weight/100 pcs: 66 lbs.

CS 810 – Diagonal Tube Brace




Part No.	A Size	Wt./100 pcs
CS 810 36	3'-0"	205
CS 810 42	3'-6"	237
CS 810 48	4'-0"	270


Note:
30° to 60° angle between the brace and channel is recommended for maximum effect.

Material: 1" dia. electric welded tubing

Stock Thickness: (.075) 14 ga.




CS 793 – Four-Hole Closed Angle Connector



"A" Angle	"B" In.
37½°	4 7/8"
45°	4 15/16"
52½°	
60°	5"
67½°	5 1/16"
75°	
82½°	


Weight/100 pcs: 100 lbs.

CS 9401 – Double Adjustable Brace



Weight/100 pcs: 307 lbs.


CS 781 – Four-Hole Open Angle Connector



"A" Angle	"B" In.
7½°	3¾"
15°	
22½°	
30°	3 11/16"
37½°	
45°	
52½°	
60°	
67½°	3 5/8"
75°	
82½°	


Weight/100 pcs: 78 lbs.

CS 9400 – Adjustable Brace



Weight/100 pcs: 307 lbs.

CS 9402 – Two-Hole Hinge Connector




"B" Bolt Size	Wt./100 pcs
½"	108
5/8"	107
¾"	106

FITTINGS


Finish: Painted Green or Electro-galvanized **Order By:** No., Size and Finish

CS 9404 – Four-Hole Hinge Connector




Part No.	Wt./100 pcs
CS 9404-1/2"	126

CS 692 – 1 5/8 inch Offset Zee Connector



Weight/100 pcs: 102 lbs.


CS 2523 – Offset Adjustable Zee Connector



Use With: CS 500, CS 520, & CS 560

Weight/100 pcs: 70 lbs.

CS 2532 – Shelf Attachment Zee




Stock Thickness: 1/8"

Use With: CS 200, CS 210

Weight/100 pcs: 9 lbs.



CS 9403 – Three-Hole Hinge Connector



"B" Bolt Size	Wt./100 pcs
1/2"	108
5/8"	107
3/4"	106



Hinge Connect or Auto-Alignment Guides -

The unique edges of the two hinges have been designed to provide an alignment guide for 0°, 45° and 90° as shown in the drawings below. This eliminates the need for measuring gages.



- Each half of the hinge is formed and welded for maximum strength.
- Hinged with Grade 5 bolt for superior strength.
- The nylon insert locknut prevents loosening of the hinge.

CS 812 – 45° Diagonal Tube Brace




A Size	Wt./100 pcs
12"	88
18"	116
24"	149
30"	181
36"	214

Design Load:
Tension = 300 lbs.
Comp. = 1,500 lbs.


Material: 1" dia. electric welded tubing
Stock Thickness: (.075) 14 ga.

CS 3060 – Offset Connector



A	Wt./100 pcs
4"	81
5"	92
6"	104
7"	115
8"	127

CS 647 – 1 7/8 inch Offset Zee Connector




Use With: CS 200, CS 210

Weight/100 pcs: 55 lbs.

FITTINGS

Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish


CS 756 – Zee Support



Use With: CS 100, CS 200 2T3, CS 210 2T3

Weight/100 pcs: 70 lbs.


CS 2601 – Zee Support



Use With: CS 150

Weight/100 pcs: 70 lbs.


CS 611 – Zee Support



Use With: CS 200, CS 210

Weight/100 pcs: 55 lbs.


CS 711 – Zee Support



Use With: CS 300

Weight/100 pcs: 53 lbs.


CS 612 – Zee Support



Use With: CS 400

Weight/100 pcs: 47 lbs.


CS 928 – Zee Support



Use With: CS 500, CS 520 and CS 560


Weight/100 pcs: 47 lbs.

CS 609 – Two-Hole Offset Plate Connector



Weight/100 pcs: 38 lbs.


CS 679 – "U" Support



Use With: CS 100, CS 200 2T3, CS 210 2T3

Weight/100 pcs: 128 lbs.


CS 2648 – "U" Support



Use With: CS 150

Weight/100 pcs: 108 lbs.


CS 613 – "U" Support



Use With: CS 200, CS 210

Weight/100 pcs: 88 lbs.


CS 2119 – "U" Support



Use With: CS 200, CS 210

Weight/100 pcs: 95 lbs.

CS 710 – "U" Support




Use With: CS 300

Weight/100 pcs: 84 lbs.

FITTINGS


Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish

CS 978 – "U" Support




Use With: CS 400
Weight/100 pcs: 71 lbs.

CS 678 – Three-Hole "U" Support




Use With: CS 150 2T3
Weight/100 pcs: 197 lbs.

CS 677 – Cup Support for Standard Single Strut




Use With: CS 200, CS 210
Weight/100 pcs: 76 lbs.

CS 735 – Eight-Hole "U" Support




Use With: CS 200, 2T3
Weight/100 pcs: 257 lbs.

CS 929 – "U" Support



Use With: CS 500, CS 520 and CS 560
Weight/100 pcs: 71 lbs.


CS 687A, CS 687B & CS 687C – Slotted "U" Support



Use With: CS 200, CS 210


Order No.	'A' Length	'B' Length	Wt./100 pcs
CS 687A	7 1/4"	4 1/8"	105
CS 687B	8 1/2"	5 3/8"	120
CS 687C	10 3/8"	7 1/4"	130

CS 733 – Six-Hole "U" Support




Use With: CS 200, CS 210
Weight/100 pcs: 171 lbs.

CS 709 – Three-Hole Offset Plate Connection




Weight/100 pcs: 58 lbs.

CS 721 – "U" Support




Use With: CS 100, CS 200 2T3, CS 210 2T3
Weight/100 pcs: 105 lbs.

CS 734 – Eight-Hole "U" Support



Use With: CS 200, 2T3
Weight/100 pcs: 209 lbs.


CS 623 – Saddle Washer



Bolt Size	Wt./100 pcs
1/4"	14
3/8"	
1/2"	
5/8"	13
3/4"	

Weight/100 pcs: 265 lbs.


CS 644 – Two-Hole Splice Clevis



Use With: CS 500, CS 520 and CS 560

Weight/100 pcs: 85 lbs.


CS 631 – Two-Hole Splice Clevis



Use With: CS 200, CS 210

Weight/100 pcs: 128 lbs.


CS 645 – Three-Hole Splice Clevis



Use With: CS 500, CS 520 and CS 560

Weight/100 pcs: 130 lbs.


CS 629 – Three-Hole Splice Clevis



Use With: CS 200 and CS 210


Weight/100 pcs: 197 lbs.

CS 616, CS 646 – Four-Hole Splice Clevis



Part No.	A	For Use With	Wt./100 pcs
CS 616	1 9/16"	CS 200, CS 210	265
CS 646	1 3/16"	CS 500, CS 560	176
CS 616-100	3 3/16"	CS 100	390
CS 616-150	2 3/8"	CS 150	390

CS 804 – Slotted Joiner



Stock Thickness: (.105)


Use With:

CS 400S, CS 500S, CS 520S and CS 560S

Note: Order CS 6072 screws & CS 6108 nuts separately.

Weight/100 pcs: 80 lbs.

CS 704 – Slotted Joiner




Stock Thickness: (.105)

Use With: CS 200S, CS 210S

Note: Order CS 6072 screws & CS 6108 nuts separately.

Weight/100 pcs: 197 lbs.

CS 1004 – Slotted Joiner




Stock Thickness: (.105)

Use With: CS 150S

Note: Order CS 6072 screws & CS 6108 nuts separately.


Weight/100 pcs: 140 lbs.

CS 993 – Inside Clevis Hanger



A Size	Wt./100 pcs
4"	78
5"	89
6"	101
7"	112
8"	124


CS 922 R or L – Two-Hole Corner Connector



Note: Specify R (Right) or L (Left) Right Hand Illustrated

Weight/100 pcs: 60 lbs.

CS 2117 R or L – Wrap-Around Corner Connector




Note: Specify R (Right) or L (Left) Right Hand Illustrated

Weight/100 pcs: 75 lbs.

FITTINGS

Finish: Painted Green or Electro-galvanized **Order By:** No., Size and Finish


CS 2128 R or L – Four-Hole Corner Connector



Note:
Specify R (Right) or
L (Left) Right Hand
Illustrated


Weight/100 pcs: 119 lbs.

CS 666 – Six-Hole Double Corner Connector




Weight/100 pcs: 115 lbs.

CS 913 – Ten-Hole Double Wing Connector




Weight/100 pcs: 193 lbs.

CS 943 – Eight-Hole Gussetted Double Corner Connector




Weight/100 pcs: 217 lbs.

CS 665 – Four-Hole Double Corner Connector




Weight/100 pcs: 76 lbs.

CS 667 – Eight-Hole Double Corner Connector



Weight/100 pcs: 155 lbs.


CS 2129 R or L – Single Corner Gussetted Connector



Note:
Specify R (Right) or
L (Left) Right Hand
Illustrated


Weight/100 pcs: 176 lbs.

CS 2514 – Eight-Hole Gussetted Double Corner Connector




Weight/100 pcs: 315 lbs.

CS 923 – Five-Hole Double Wing Connector




Weight/100 pcs: 93 lbs.

CS 821 – Eight-Hole Double Wing Connector




Weight/100 pcs: 150 lbs.

CS 945 – Ten-Hole Gussetted Double Wing Connector



Weight/100 pcs: 274 lbs.

CS 668 – Six-Hole Triple Wing Connector




Weight/100 pcs: 113 lbs.

FITTINGS


Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish

CS 670 – Nine-Hole Triple Wing Connector




Weight/100 pcs: 177 lbs.

CS 669 – Twelve-Hole Triple Wing Connector



Weight/100 pcs: 230 lbs.



CS 3041 – Double-Column Post Base




Use With: CS 100, CS 200 2T3, and CS 210 2T3.

Weight/100 pcs: 116 lbs

CS 3013, 3013 SQ – Post Base




(CS 3013)



(CS 3013 SQ)



Weight/100 pcs: 307 lbs.

CS 3040 – Post Base




Weight/100 pcs: 297 lbs.

CS 3025, CS 3025 FL – Post Base




(CS 3025)





(CS 3025 FL)

Weight/100 pcs: 358 lbs.


CS 2064 – Double-Column Post Base



CS 3033, CS 3033 SQ – Post Base




(CS 3033)



(CS 3033 SQ)

Weight/100 pcs: 373 lbs.




Use With: CS 100, CS 200 2T2, CS 200 2T3, CS 200 2T4 and CS 200 2T5

Weight/100 pcs: 311 lbs.


FITTINGS

Finish: Painted Green or Electro-galvanized Order By: No., Size and Finish


CS 3029 – Double-Column Post Base




CS 3064 – Double-Column Post Base




CS 2521 – Two-Wheel Trolley




CS 2528 – Trolley Beam Standard Support




CS 2528 1 – Trolley Beam Heavy Support and Track Joiner



CS 2524 – Two-Bearing Light Duty Trolley



CS 2525 – Four-Bearing Light Duty Trolley



CS 2522 – Four-Wheel Trolley

